

The Exinda Appliance 10064 is Exinda's mid-large range data center grade appliance. Architected to serve the large data centers and service provider networks, the 10064 is built to scale with your business. With exceptional power and bandwidth capacity, this appliance can protect application SLAs no matter what the network throws at it. Built for companies and service providers with extremely high traffic volume and whose business depends on meeting and exceeding network application SLAs.

Traffic Shaping	
Shaping Throughput	10 Gbps
Concurrent Flow	1,200,000
New Connection Rate	32,000/s
Packets Per Second	1,400,000/s
Traffic Policies	4096
Traffic Acceleration	
Acceleration Throughput	500 Mbps
Edge Cache Throughput	250 Mbps
Optimized Connections	32,000
Network Diagnostics	
APS Objects	300
SLA Objects	300
PDF Reports	100
Interface Capabilities	
Built in NICs	None
Additional NIC Slots	4 half height, 1 full height
Available NICs	Copper: 9 x 1G bypass bridge pair, 2 x 10G bypass bridge pair Fiber: 5 x 1G bypass bridge pair, 2 x 10G bypass bridge pair
Management Ports	DB-9 serial console and dedicated RJ-45 management interface
IPMI	Dedicated RJ-45 interface
Physical Characteristics	
Form Factor	Desktop or 2U rack mount
Dimensions (HxWxD)	86.8mm x 482mm x 682mm (3.41" x 18.97" x 26.84")
Power	Dual hot-plug redundant power - 750W
Power Rating	100–240 V AC, 50/60 Hz autoranging, 5A - 10.5A
Weight*	40.6 lbs (18.4 kg)
Data Store/Cache Size	1.8 TB, RAID 10
Environment	10°C to 35°C (50°F to 95°F), 10% to 80% relative humidity

* The weight can be higher in case of different hardware configuration.