

The Exinda Appliance 10064 is Exinda's mid-large range data center grade appliance. Architected to serve the large data centers and service provider networks, the 10064 is built to scale with your business. With exceptional power and bandwidth capacity, this appliance can protect application SLAs no matter what the network throws at it. Built for companies and service providers with extremely high traffic volume and whose business depends on meeting and exceeding network application SLAs.

| <b>Traffic Shaping</b>          |                                                                                                                                             |
|---------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------|
| Shaping Throughput              | 10 Gbps                                                                                                                                     |
| Concurrent Flow                 | 1,200,000                                                                                                                                   |
| New Connection Rate             | 32,000/s                                                                                                                                    |
| Packets Per Second              | 1,400,000/s                                                                                                                                 |
| Traffic Policies                | 5100                                                                                                                                        |
| <b>Traffic Acceleration</b>     |                                                                                                                                             |
| Acceleration Throughput         | 500 Mbps                                                                                                                                    |
| Edge Cache Throughput           | 250 Mbps                                                                                                                                    |
| Optimized Connections           | 32,000                                                                                                                                      |
| <b>Network Diagnostics</b>      |                                                                                                                                             |
| APS Objects                     | 300                                                                                                                                         |
| SLA Objects                     | 300                                                                                                                                         |
| PDF Reports                     | 100                                                                                                                                         |
| <b>Interface Capabilities</b>   |                                                                                                                                             |
| Built in NICs                   | None                                                                                                                                        |
| Additional NIC Slots            | 4 half height, 1 full height                                                                                                                |
| Available NICs                  | <b>Copper:</b> 9 x 1G bypass bridge pair, 2 x 10G bypass bridge pair<br><b>Fiber:</b> 5 x 1G bypass bridge pair, 2 x 10G bypass bridge pair |
| Management Ports                | DB-9 serial console and dedicated RJ-45 management interface                                                                                |
| IPMI                            | Dedicated RJ-45 interface                                                                                                                   |
| <b>Physical Characteristics</b> |                                                                                                                                             |
| Form Factor                     | Desktop or 2U rack mount                                                                                                                    |
| Dimensions (HxWxD)              | 86.8mm x 482mm x 682mm (3.41" x 18.97" x 26.84")                                                                                            |
| Power                           | Dual hot-plug redundant power - 750W                                                                                                        |
| Power Rating                    | 100–240 V AC, 50/60 Hz autoranging, 5A - 10.5A                                                                                              |
| Weight*                         | 40.6 lbs (18.4 kg)                                                                                                                          |
| Data Store/Cache Size           | 1.8 TB, RAID 10                                                                                                                             |
| Environment                     | 10°C to 35°C (50°F to 95°F), 10% to 80% relative humidity                                                                                   |

\* The weight may be weight can be higher in case of different hardware configuration.



**Talk to an Exinda appliance expert today**

[sales@gfi.com](mailto:sales@gfi.com)

[www.gfi.com/exinda](http://www.gfi.com/exinda)